
## Product Specification Chart



Custom colors available upon request

	RESIDENTIAL - 5/8"	COMMERCIAL -3/4"	COMMERCIAL PLUS HEAVY DUTY	INDUSTRIAL -1"
	6' WIDE PANELS*	6' WIDE PANELS*	8' WIDE PANELS*	6' WIDE PANELS*
	*panel width nominal	*panel width nominal	*panel width nominal	*panel width nominal
POSTS	2" x .060 WALL	2-1/2" x .075 WALL	2-1/2" x .075 WALL	2-1/2" x .075 WALL
	2" x .125 WALL	2-1/2" x .125 WALL	2-1/2" x .125 WALL	2-1/2" x .125 WALL
	2-1/2" x .075 WALL			3" x .125 WALL
	2-1/2" x .125 WALL			
HORIZONTAL RAILS	1" x 1-1/8 "	1-1/4" x 1-1/4"	1-1/4" X 1-1/4"	1-5/8" X 1-5/8 "
SIDE WALLS	.080	.100	.100	.100
TOP WALLS	.060	.070	.070	.075
PICKETS	5/8" x 5/8" x .050 WALL	3/4" x 3/4" x .050 WALL	3/4" x 3/4" x .050 WALL	1" x 1" x .060 WALL
PICKET SPACING	3-7/8"	3-7/8"	3-7/8"	3-7/8"
HEIGHTS	3', 4', 54", 5', 6 '	3', 4', 5', 6 '	4', 5', 6 '	4', 5', 6 '
COLORS	BLACK, WHITE, PEWTER	BLACK, WHITE, PEWTER	BLACK, WHITE, PEWTER	BLACK, WHITE, PEWTER
CUSTOM ORDER	ALL COLORS	ALL COLORS	ALL COLORS	ALL COLORS
SCREWS	302 STAINLESS STEEL	302 STAINLESS STEEL	302 STAINLESS STEEL	302 STAINLESS STEEL
FINISH	ARMOUR GUARD	ARMOUR GUARD	ARMOUR GUARD	ARMOUR GUARD

American Owned American Made Exclusive Armour Shield™ powder coated finish 12 step process





Every Fence panel is assembled with stainless steel, corrosion resistant screws. All fence components have a minimum ultimate yield strength of 35,000 PSI. All our Walk and Drive gates are welded for maximum strength.



